

CriticalConneX™ CC1100



The CC1100 is part of the new generation of TAP products from Network Critical; it is a fully featured, fully configurable tapping solution for 10/100 network links, with support for up to 2 network tools.

The CC1100 features Network Critical's innovative Zero-packet-loss failsafe technology which maintains full-duplex pass-through capability to protect your network link from downtime in the event of a product failure.

The CC1100 features several configurable operation modes for flexible deployment:


- the traffic that is seen at each monitoring port can be selected as A, or B, or A+B, which means the CC1100 can function as a breakout tap or as a dual-port aggregation tap.
- Packet Injection (PI) allows network tools to inject packets into the live network so that an IPS can mitigate attacks.
- Link Failure Propagation (LFP) allows simultaneous failover of network interfaces, useful in HA network scenarios.

The CC1100 is available in a portable, stand-alone form factor or as a plug-in module for the CriticaConneX™ enterprise chassis.


Model Options

- CC1100 CriticalConneX 10/100 TAP Module with 2 configurable monitor ports, for installation into CC1000 modular chassis
- P Portable form factor with external power supplies, rack mountable using CC1003 racking plate
- HA High Availability (HA) option, no pass-through on network ports also means you can aggregate 2 switch SPAN ports
- S Secure option, Packet Injection permanently disabled.

Deployment



In **BREAKOUT** mode bi-directional live network traffic is broken-out onto separate monitor ports, giving a single network tool full access to the traffic. This type of deployment is recommended when 100% guaranteed traffic capture is required.



In **COMBI** mode bi-directional live network traffic is combined onto each monitor port, in this way two network tools can be given access to the traffic. This type of deployment is recommended for edge links where traffic levels are lower.

Features



- One-To-Many** - mirrors a single network link to multiple network tools
- A/B Breakout** - breaks out the network traffic into two separate streams
- A+B Combi** - combines the network traffic into a single stream
- Packet Injection** - allows the network tool to inject packets into the live link
- 10BASE-T** - supports 10Mbit/s Ethernet networks
- 100BASE-TX** - supports 100Mbit/s Fast Ethernet networks

Technical Specs

Operating Specs

Operating Temperature: 0°C to 58°C
 Storage Temperature: -12°C to 72°C
 Relative Humidity: 10% to 95%
 Non condensing

Cable Interface

Copper cable type: 22-24 AWG UTP
 CAT5/CAT5E
 Link distance supported: 100 Meters

Connectors

Network Ports: 2 x RJ45 Pass through
 Monitor Ports: 2 x RJ45 Configurable